

KMZ

Metal flat filter cell with U-section galvanised steel frame and double electrowelded galvanised wire mesh that supports the filter fabric made up of layers of metal mesh in galvanised steel capped braid.

TECHNICAL SPECIFICATIONS AND USAGE LIMIT				
EFFICIENCY class (EN ISO 16890:2016)	Group ISO COARSE (ePM1 = 1% - ePM2,5 = 2% - ePM10 = 12%)			
EFFICIENCY class (CEN EN779-2012)	G2			
	65% for filter 10mm thickness			
AVERAGE gravimetric efficiency:	70% for filter 23mm thickness			
	75% for filter 48mm thickness			
MAXIMUM WORKING temperature:	100°C			
RELATIVE humidity:	100%			
	5 Pa for filter 10mm thickness			
INITIAL pressure drop:	10 Pa for filter 23mm thickness			
	15 Pa for filter 48mm thickness			
RECOMMENDED final pressure drop:	150 Pa			
MAXIMUM pressure drop:	300 Pa			
RECOMMENDED frontal air speed:	1,5 m/s			

SELECTION CHART							
Length [mm]	Width [mm]	Filtering Surface [m²]	Nominal Flow Rate [m³/h]				
250	500	0,12	700				
287	592	0,17	900				
400	400	0,16	850				
400	500	0,20	1.100				
400	625	0,25	1.350				
500	500	0,25	1.350				
500	625	0,31	1.700				
592	592	0,35	1.900				

Frame Thickness [mm]	Layers of Braid [n]
10	2
23	4
48	6



FILTERING MEDIA

The filtering media is composed of layers of metal mesh in galvanised steel capped braid.

APPLICATIONS

Prefiltration in high-efficiency filters, filtration of dry dust and oil mist, treatment of airborne fumes and greases.

PRODUCT DISPOSAL

Dispose of the product by separating the metal part from the filtering part. The CER code for disposal of the metal part is 120101. Warning: declare whether the filter to be disposed of contains toxic substances

GREEN BUILDING

Thanks also to the support of GreenMap, products manufactured by Tecnica contribute to obtain the credits of the major international rating systems for sustainable buildings:



Contributes to credits: IP, EA, MR



Contributes to credits: MATERIALS, COMMUNITY **BREEAM**®

BREEAM

Contributes to credits: MAN, WST

For further details regarding the specific contributions to the credits indicated, contact Tecnica SrI

APPLICATIONS								
	118		REACH	RoHS	ĺη		*	*
OEM	Residential	Easy Pack	REACH Certificate	RoHS Certificate	Industry	Building	Air conditioning	CMV

*On request

